



Declaration of Performance

according Annex III of the Regulation (EU) No 305/2011

CALSITHERM

Revision 1.0.0

Date of issue: 29.07.2015

Silcaheat 600 C

No. 2015-CS-MD-14-1.3

1. Unique identification code of the product-type:

**Calcium Silicate Silcaheat 600 C
Construction board for fireplaces**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number is stamped on the side

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification EN 14306:2009+A1:2013, as foreseen by the manufacturer:

**Thermal insulation products for building equipment
and industrial installations**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Silcaheat 600 C

**Calsitherm Silikatbaustoffe GmbH
An der Eiche 15
D-33175 Bad Lippspringe
Tel.: +49 5254 990 92 0
Fax: +49 5254 990 92 17
E-Mail: info@calsitherm.de**

5. When applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body **Materialprüfungsamt Nordrhein-Westfalen (Notified Body No. 0432)** performed the initial type testing of the product and issued the **test report No. 420002528 14-1.3** on 30.06.2015. The notified body **Materialprüfungsamt Nordrhein-Westfalen, Außenstelle Erwitte**, evaluated the class of the construction material and issued the **report of classification 230009943-09** on 07.07.2015. The manufacturer performs ongoing monitoring, evaluation and affirmation of factory production control.

8. In case of a construction product for which a European Technical Assessment has been issued:

not relevant

9. Declared performance

| Essential characteristics | Performance | Harmonised technical specification |
|---|--|------------------------------------|
| Reaction to fire | A1 | EN 14306:2009+A1:2013 |
| Water vapour diffusions resistance | --- | |
| Compressive strength | CS(10) 5000 (≥ 5000 kPa) | |
| Rate of water soluble -chlorides -fluorides | 15.3 mg/kg Lower than detection limit | |
| pH-value | 9.3 | |
| Release of dangerous substances | No test method available | |
| Continous glowing combustion | No test method available | |
| Thermal conductivity | 200°C 0.18 W/mK 400°C 0.19 W/mK 500°C 0.19 W/mK 800°C 0.26 W/mK | |
| Dimensions | Is given on the packaging, tolerance class +/- 3 mm | |
| Maximum service temperature | ST(+) 1000 ($\geq 1000^\circ\text{C}$) | |
| Minimum service temperature | No performance determined | |
| Dimensional stability Length Width Thickness | -0.05 % -0.03 % -0.06 % | |
| Short term water absorbtion by partial immersion | 23.97 kg/m ² | |

10. The performances of the products identified in points 1 and 2 are in conformity with the declared performances in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr. Tobias Hölscher
(Managing Director)

Paderborn-Sennelager, 29.07.2015

